

TWR Lighting, Inc.TM

*Enlightened Technology*SM

LED RED FAA TYPE L-864 BEACON MODEL LEDBEACON2

INTENSITY:	MEDIUM
HORIZONTAL COVERAGE:	360°
VERTICAL BEAM:	3° MIN.
FRESNEL OPTICS:	300 mm LENS
LAMP DESCRIPTION:	LED
EFFECTIVE CANDELAS (NIGHT):	2,000 ± 25%
FLASHHEAD DIMENSIONS:	17-½" x 15" (44.45 x 38.1 cm)
FLASHHEAD MATERIAL:	ACRYLIC
FLASHHEAD BASE MATERIAL:	ALUMINUM / BLUE POWDER COAT
POWER REQUIREMENTS:	90V-240V AC 50/60Hz
WATTAGE:	40 WATT
WEIGHT:	46 lbs. (20.89 kg)
OPERATING TEMPERATURE:	-55°C TO +55°C
WIND LOAD:	CAAA = 1.2 ft ²
MOUNTING HOLES:	4 11/16" HOLES SPACED 90° ON 13-1/4" (33.65 cm) BOLT CIRCLE

CREATES NO EMI/RFI

CAN BE FLASHED OR STEADY BURNED.



**USES 90% LESS ENERGY THAN AN
INCANDESCENT.**

FOR MORE INFORMATION CONTACT US AT:

4300 Windfern Rd. #100 Houston, Tx. 77041-8943
Ph: 713-973-6905 Fax: 713-973-9352
Web Address: <http://www.twrlighting.com>
Email: sales@twrlighting.com
©2007 TWR Lighting, Inc.

TWR Lighting, Inc.TM
*Enlightened Technology*SM

PF20059